

Ad sizing requirements are listed below. Remember to allow for bleed (.125 inches beyond trim).


## submitting print-ready ads:

- + Final high-res CMYK PDFs.
- + All PDF files must meet PDF/X-1A standards at 300dpi.
- + Make sure all high-resolution images and fonts, in the native application file, are linked before creating the PDF.
- + All fonts must be fully embedded (no subsets) in the PDF document.
- + All files must be CMYK, we do not accept RGB.
- + Do not use Spot Colors.

## file submission:

Send your  
Print-Read ad to David Schner  
dschner@leadersmag.com

Production assistance - Darrell Brown  
dbrown@leadersmag.com



## single page dimensions

TRIM SIZE	10" x 12"
BLEED SIZE	10.25" x 12.25"
LIVE AREA	9" x 11" (keep all text/logos within this area)



### TEXT AREA MARGINS

TOP	.5"
BOTTOM	.5"
SIDES	.5"

Bleed area must be  
.125 inches beyond trim

## two-page spread dimensions

TRIM SIZE	20" x 12"
BLEED SIZE	20.25" x 12.25"
LIVE AREA	18" x 11" (keep all text/logos within this area)



### TEXT AREA MARGINS

TOP	.5"
BOTTOM	.5"
SIDES	.5"

Bleed area must be  
.125 inches beyond trim